

## FOAM-BASED PORTABLE EXTINGUISHERS (SPRAY MODEL)


#### **PRODUCT OVERVIEW**


The quickest way to kill a fire is to not let it feed off the oxygen in the vicinity. The Foam Extinguishers work on the simple principle of cutting off the supply of oxygen required to sustain a fire. The foam smothers the flames and forms a compact blanket over the fire, preventing it from spreading or re-igniting.


Ceasefire's Foam Spray model extinguishers form a foam blanket, cutting down on the oxygen supply. It works on Class A, B, F, and Electrically started fires. The squeeze grip mechanism makes them faster and easier to use.





#### **ENGINEERING DRAWINGS**
















## **TECHNICAL SPECIFICATIONS**

Product Code	UOM	CF-000779SA	CF-000805SA	CF-000715SA	CF-000806SA	CF-000716SA	CF-000807SA
Description	-	Fire Ext Foam 3L SS SP Red (Spray model) (C)	Fire Ext Foam 3L MS SP Red (Spray model) (C)	Fire Ext Foam 6L SS SP Red (Spray model) (C)	Fire Ext Foam 6L MS SP Red (Spray model) (C)	Fire Ext Foam 9L SS SP Red (Spray model) (C)	Fire Ext Foam 9L MS SP Red (Spray model) (C)
Capacity of Agent	L	3-5%	3-5%	6-5%	6-5%	9-5%	9-5%
Certification	-	BS EN3 - LPCB EU-MED UKCA-MER PED UKCA-PED					
Diameter of Shell	ММ	140	140	160	160	175	175
Total Height (approx.)	ММ	435	440	520	520	610	615
MOC of Shell	-	SS 304 (1.4301)	Steel Cr2(DC01)	SS 304 (1.4301)	Steel Cr2 (DC01)	SS 304 (1.4301)	Steel Cr2 (DC01)
Min. Wall Thickness	ММ	1.5	1.6	1.5	1.6	1.5	2
Test Pressure	BAR	35	35	35	35	35	35
Anti-Corrosive Treatment	_	Outer & Inner surfaces were EP Powder coated having Thickness 50 Micron Min. RAL Shade 3000	Outer & Inner surfaces were EP Powder coated having Thickness 50 Micron Min. RAL Shade 3000	Outer & Inner surfaces were EP Powder coated having Thickness 50 Micron Min. RAL Shade 3000	Outer & Inner surfaces were EP Powder coated having Thickness 50 Micron Min. RAL Shade 3000	Outer & Inner surfaces were EP Powder coated having Thickness 50 Micron Min. RAL Shade 3000	Outer & Inner surfaces were EP Powder coated having Thickness 50 Micron Min. RAL Shade 3000
Service Pressure	BAR	15	15	15	15	15	15
Type of Operating Mechanism	-	Squeeze Grip with NRV and Burst Disc.					
Type of Pressure Gauge	-	Magnetic Bourdon Tube Type					



Product Code	UOM	CF-000779SA	CF-000805SA	CF-000715SA	CF-000806SA	CF-000716SA	CF-000807SA
Type of Dis. Fitting & Length	ММ	EPDM Rubber Braided Hose Pipe with nozzle Length of Hose 300mm (Min.)	EPDM Rubber Braided Hose Pipe with nozzle Length of Hose 300mm (Min.)	EPDM Rubber Braided Hose Pipe with nozzle Length of Hose 500mm (Min.)	EPDM Rubber Braided Hose Pipe with nozzle Length of Hose 500mm (Min.)	EPDM Rubber Braided Hose Pipe with nozzle Length of Hose 500mm (Min.)	EPDM Rubber Braided Hose Pipe with nozzle Length of Hose 500mm (Min.)
Throw	METER	5	5	5	5	6	6
Min. Discharge Time	SEC.	9	9	15	15	15	15
Fire Rating	-	8A   89B	8A   89B	13A   144B	13A   144B	21A   233B	21A   233B
Operating Temperature Range	°C	From +5°C to +60°C					
Applicable to Type of Fire	-	A, B	A, B	A, B	A, B	А, В	A, B
Filled Weight Range*	KG	Approx. 5.70	Approx. 5.75	9.40 to 9.73	9.40 to 9.73	13.05 to 13.95	14.70 to 15.15
Packed Weight Range (approx)**	KG	Approx. 7	Approx. 6	Approx. 10.2	Approx. 10.1	Approx. 14	Approx. 15.3 kg
Packed Size Length x Width x Height	ММ	160 x 160 x 470	160 x 160 x 470	230 x 220 x 670	230 x 220 x 670	190 x 195 x 650	190 x 195 x 650
Product Warranty	YEAR	5	5	5	5	5	5

<sup>\*\*</sup>It includes Empty Extinguisher, Contents, Plastic Base, Hose / Horn and bracket.

 $<sup>\</sup>hbox{\tt ***It includes Empty Extinguisher, Contents, Packaging, \ Plastic Base, Hose / Horn and bracket.}$ 



## **CERTIFICATIONS**













<sup>\*</sup>v3' Published Date is 17-04-2025.

# **CEASEFIRE INDUSTRIES UK LIMITED**

Call us at: 0-113-868-6666, 0-126-891-9999 www.ceasefire.co.uk

<sup>\*\*</sup>Regular R&D and product improvisations may lead to change in product specifications in this data sheet, without any prior notice.